

standard type male

Bend protection sleeve for cable Ø 5.00mm standard, others on request.

front views

standard type female

Bend protection sleeve for cable Ø 5.00mm standard, others on request.

front views

„Quick Lock“ type male

Bend protection sleeve for cable Ø 6.50mm standard, others on request

front views

Any cable assembly available on request.

Connectors at both ends as well as cable length and quality as per your specification possible.

Please contact the nearest E-tec sales office or Distributor.

SPECIFICATIONS

Current rating	1 A max. at 100 V AC or 2 A max. at 12 V DC	Withstanding voltage	250 V AC for 1 min.	Insulator material (RoHS compliant)	Nylon UL 94 V-0
Insulator resistance	50 MΩ min. at 250 V DC	Operating temperature	-55°C to +85°C	Insertion force	4.5kg max.
Contact resistance	30 mΩ max.	Contact material (RoHS compliant)	Brass	Extraction force	0.8kg min.
		Contact plating	Silver; MQ Type = Gold	Insertion/extraction cycles	500 min.

Ordering Code

MDP - xxx - XX 01 - xx

Nbr of contacts	Types	Plating
003 to 009 except MQ Type	MA = male standard FA = female standard MQ = male „Quick Lock“	MA & FA Type: AGZ = silver MQ Type only: 55 = gold