


REV.	DESCRIPTION	DATE	DRAWN
A	New	08.12.2016	Cherry
B	General update	04.07.2019	Cheng



Order Code
M12-MA08-CVFP-55/00


Specifications

Electrical
 Current rating: 2A per contact
 Insulation resistance: 100MΩ min.
 Voltage rating: 30V AC/DC
 Withstanding voltage: 650V AC

Mechanical Requirements

Waterproof rate: IP68
 Recommended panel thickness: 0.8 to 5.0mm
 Recommended torque: 9~10 kgf-cm
 Operating life: 100 cycles min.

In accordance with IEC 61076-2-101:2012



Item	Part Name	Materials / Finish(Color)	Q'TY
1	Contact	Copper Alloy / Au Plated	8
2	Housing	Thermoplastic / Black	1
3	Metal Body	Copper Alloy / Ni Plated	1
4	Hex Nut	Copper Alloy / Ni Plated	1
5	O-Ring	NBR / Black	1
6	Glue	Epoxy / Black	-

E-tec 2019 © - all rights reserved



UNIT	mm	GENERAL TOLERANCE		DRAWN	Cherry	DATE	08.12.2016
SCALE	Free	X.° ±	X. ±	CHECK	Cheng	DATE	04.07.2019
		.XX° ±	.XX ± 0.20	APPROVE	Fagi	DATE	04.07.2019
		.XXX° ±	.XXX ±				

DWG. NO.	M12-MA08-CVFP-55/00	SHEET	1/1
SERIES NO.	M12-MA08-CVFP-55/xx	REV.	B

M12 Circular Connector
8-Pin Male A - Coding Type
 Solder Cup - Panel Front Mount