


REV.	DESCRIPTION	DATE	DRAWN
A	New	28.12.2016	Cherry
B	General update	02.07.2016	Cheng



Order Code

MCC-M08MA03/XxxXXxx-xxxx-00

Cable Length "L"
0001 ~ 9999cm

P2 End Type

- 0 = Loose cable end
- M08MA03** = M08 3-pin male A-Coding
- M08FA03** = M08 3-pin female A-Coding
- Others on request

Specifications

Electrical

Current rating: 3A per contact
 Insulation resistance: 100MΩ min.
 Voltage rating: 60V AC/DC
 Withstanding voltage: 1000V AC

Mechanical Requirements

Waterproof rate: IP68
 Operating life: 100 cycles min.

In accordance with IEC 61076-2-104:2014

P1

- 1 Black
- 3 Brown
- 4 Red

Item	Part Name	Materials/Finish(Color)	Q'TY
1	Contact	Copper Alloy / Au Plated	3
2	Bush	Copper Alloy / Ni Plated	1
3	Screw Nut	M8X1, Copper Alloy / Ni Plated	1
4	Over Mold	PVC / Black	1
5	Cable	UL2464, 3C, 22AWG, OD Ø5.0±0.2mm / Black, Separator: Talc(UV)	1

E-tec 2019 © - all rights reserved



UNIT	mm	CABLE LENGTH TOLERANCE	DRAWN	Cherry	DATE	28.12.2016
SCALE	Free	0 ~ 200mm -> ±10mm	CHECK	Cheng	DATE	02.07.2019
		201 ~ 1000mm -> ±20mm	APPROVE	Fagi	DATE	02.07.2019
		1001 ~ 1500mm -> ±25mm				
		1501 ~ 2100mm -> ±30mm				
		2100mm † -> ±40mm				

DWG. NO.	MCC-M08MA03/M08MA03	SHEET 1/1
SERIES NO.	MCC-M08MA03/XxxXXxx	REV. B

M08 Cable Assembly
3-Pin Male A - Coding
 Single / Double Ended