


REV.	DESCRIPTION	DATE	DRAWN
A	New	28.12.2016	Cherry



Order Code

MCC-M12FA04/XxxXXxx-xxxx-00



Cable Length "L"
0001 ~ 9999cm

P2 End Type

- 0 = Loose cable end
- M12FA04 = M12 4-pin female A-Coding
- M12MA04 = M12 4-pin male A-Coding
- Others on request

Specifications
Electrical

Current rating: 4A per contact
Insulation resistance: 100MΩ min.
Voltage rating: 250V AC/DC
Withstanding voltage: 1400V AC

Mechanical Requirements

Waterproof rate: IP68
Operating life: 100 cycles min.

In accordance with IEC 61076-2-101:2012

P1

1		Brown
2		Orange
3		Black
4		Red

Item	Part Name	Materials / Finish(Color)	Q'TY
1	Contact	Copper Alloy / Au Plated	4
2	O-Ring	Silicone / Red	1
3	Housing	Thermoplastic / Black	1
4	Screw Nut	M12X1, Copper Alloy / Ni Plated	1
5	Over Mold	PVC / Black	1
6	Cable	UL2464, 4C, AWG #22, OD Ø5.0±0.2mm / Black, Separator: Talc(UV)	1

E-tec 2019 © - all rights reserved



UNIT	mm	CABLE LENGTH TOLERANCE	DRAWN	Cherry	DATE	28.12.2016
SCALE	Free	0 ~ 200mm -> ±10mm	CHECK	Cheng	DATE	01.07.2019
		201 ~ 1000mm -> ±20mm	APPROVE	Fagi	DATE	01.07.2019
		1001 ~ 1500mm -> ±25mm				
		1501 ~ 2100mm -> ±30mm				
		2100mm † -> ±40mm				

DWG. NO.	MCC-M12FA04/M12FA04	SHEET 1/1
SERIES NO.	MCC-M12FA04/XxxXXxx	REV. B

M12 Cable Assembly
4-Pin Female A - Coding
Single / Double Ended