







# 1.27mm Pin Header & Board Spacer

## 1.27mm x 2.54mm Board Spacer



**SL1**

**SL2**

**SP1**

**SP2**



### Specifications

Current rating	1 A
Insulation resistance	1000 MΩ min.
Withstanding voltage	500 V AC
Operating temperature	- 40°C to +105°C
Contact material (RoHS compliant)	Copper Alloy
Insulator material (RoHS compliant)	PA6T UL 94 V-0

### PCB Hole Layout

single row

dual row



### How to order

**S** xx - xxx - S xxx/xx - **55/1**

Rows single plastic	Nbr of pins	Pin code	DIM "A"	DIM "B"	Plating
<b>L1</b> = single row	single row = <b>003</b> to <b>050</b>	<b>079/01</b>	2.80 mm	2.60 mm	
<b>L2</b> = dual row	dual row = <b>006</b> to <b>100</b>	<b>091/02</b>	4.00 mm	2.60 mm	
		<b>111/01</b>	6.00 mm	2.60 mm	
		<b>164/01</b>	2.50 mm	11.40 mm	
		<b>179/01</b>	12.30 mm	3.10 mm	
		other dimensions on request			
Rows Boardspacer	Nbr of pins	Pin code	DIM "A"	DIM "B"	DIM "C"
<b>P1</b> = single row	single row = <b>003</b> to <b>050</b>	<b>084/01</b>	1.10 mm	1.30 mm	6.00 mm
<b>P2</b> = dual row	dual row = <b>006</b> to <b>100</b>	<b>116/01</b>	2.80 mm	2.60 mm	6.20 mm
		<b>152/01</b>	6.00 mm	3.00 mm	6.20 mm
		<b>127/01</b>	2.20 mm	2.20 mm	8.30 mm
		<b>137/01</b>	3.00 mm	2.30 mm	8.40 mm
		<b>160/06</b>	3.00 mm	4.00 mm	9.00 mm
		<b>210/06</b>	5.50 mm	2.50 mm	13.00 mm
		<b>218/01</b>	6.00 mm	1.80 mm	14.00 mm
		other dimensions on request			